

Однооборотный и многооборотный энкодер AD58S DRIVE-CLiQ

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: hro@nt-rt.ru || сайт: <https://hengstler.nt-rt.ru>

TECHNICAL DATASHEET

Motor Feedback Absolute Encoder AD58S DRIVE-CLiQ



AD58S DRIVE-CLiQ

TECHNICAL DATA mechanical

- Singleturn and Multiturn Encoder for high performance motion control
- Encoder for Functional Safety applications (SIL2 PLd, category 3)
- Resolution: up to 24 Bit ST + 12 Bit MT
- DRIVE-CLiQ interface
- Wide operating temperature range
- Up to 10,000 rpm continuous operation
- Motor Temperature Logging and Temperature Monitoring of Encoder
- Optical encoder with a true geared multiturn

ACURO®
drive



Housing Diameter	58 mm		
Shaft Diameter	9.25 mm tapered Solid Shaft; Taper 1:10		
Flange (Mounting of Housing)	Spring Tether		
Protection Class Shaft Input (EN 60529)	IP50		
Protection Class Housing (EN 60529)	IP50		
Axial End Play of Mating Shaft (static)	± 0.5 mm		
Radial Runout of Mating Shaft (static)	± 0.05 mm		
Speed max.	10,000 rpm		
Starting Torque typ.	≤ 1.5 Ncm		
Moment of Inertia	3.1 x 10 ⁻⁶ kgm ²		
Vibration Resistance (EN 60068-2-6)	100 m/s ² (50 ... 2000 Hz)		
Shock Resistance (EN 60068-2-27)	1000 m/s ² (6 ms)		
Operating Temperature ¹	-25 °C ... +110 °C		
Storage Temperature ²	-20 °C ... +80 °C		
Relative Humidity (EN 60068-2-78)	≤ 90 % ; without condensation		
Measurement Point External Tem- perature Sensor	Type	KTY84-130	PT1000
	Temp. Measurement Range ³	-40 °C ... +200 °C	
	Resolution	0,2 K	0,2 K
Material Shaft	Stainless Steel		
Material Housing	Aluminum		
Weight	approx. 260 g (Singleturn) / 310 g (Multiturn)		
Connection	Data Connector Encoder axial 8-pole Motor winding temperature sensor input axial 2-pole		

¹ measured at TM, see dimensional drawing

² due to packaging

³ calibration temperature 100 °C

TECHNICAL DATASHEET

Motor Feedback Absolute Encoder AD58S DRIVE-CLiQ

TECHNICAL DATA electrical

General design	as per EN IEC 61010-1, protection class III, contamination level 2, overvoltage class II
Supply Voltage	10-36 VDC
Power Consumption max.	2.5 W (at 24 V)
Current Consumption typ.	40 mA (at 24 V Singleturn) 60 mA (at 24 V Multiturn)
Interface / Protocol	DRIVE-CLiQ
Siemens-Software (Version: 12.2.2014)	Sinamics Simotion: ≥ V4.4 HF4 Sinumerik with safety: : ≥ V4.4 SP2
Resolution Singleturn	20 Bit 24 Bit
Resolution Multiturn	12 Bit
Absolute Accuracy	± 35" (at 20 Bit) ± 25" (at 24 Bit)
Cable Length	≤ 95 m

TECHNICAL DATA safety


Design Functional Safety	SIL2 according to EN IEC 61508, 62061, 61800-5-2, 61800-5-3 PLd according to EN ISO 13849-1
Resolution for save position	9 Bit Singleturn
PFH-value	5.26×10^{-8} per hour (85°C)
MTTFd	169 years
DCavg	90%
Safe Position ¹	Encoder: 2° (Safety relevant measuring step: SM = 0,7°)
Realizable safety function according to EN 61800-5-2	SS1 (Safe Stop 1) ² SS2 (Safe Stop 2) ² SOS (Safe Operating Stop) SDI (Safe direction) SLS (Safe limited speed) SLI (Safe limited increment) SLA (Safe limited acceleration) SSR (Safe speed range) SAR (Safe acceleration range) SLP (Safe limited position) ³ SCA (Safe cam) ³

¹ Further tolerances may occur in subsequent electronics after position value comparison (contact manufacturer of subsequent electronics)


² deceleration controlled (-d) or ramp monitored (-r)

³ For SLP and SCA functions a safe reference run must be performed after „Power ON“ (see integration manual 0 580 935, chapter 8.1.2, S. 22)

ELECTRICAL CONNECTIONS PCB Connector, 8-pole



ELECTRICAL CONNECTIONS PCB Connector, 2-pole Temperature Sensor




PIN	Signals
1a	RX-N
2a	RX-P
3a	TX-P
4a	TX-N
1b	Screen
2b	N.C.
3b	UB -
4b	UB +

PIN	Signals
1	T +
2	T -

TECHNICAL DATASHEET

Motor Feedback Absolute Encoder AD58S DRIVE-CLiQ

DIMENSIONAL DRAWING



TM: Measuring point temperature

- 1: Mounting screw for cover. Torx TX10, tightening torque 0.8±0.1Nm
- 2: Cover
- 3: PCB connector 8 pole
- 4: KTY connector 2 pole
- 5: Cable outlet KTY
- 6: Cable outlet PCB connector
- 7: Back-off thread M6 / screw min. M6x60
- 8: Mounting screw DIN912 M5x70 - A2-70, tightening torque 3.5±0.5Nm


Connection is to be used as a materially bonding anti-rotation lock

Dimensions in mm

TECHNICAL DATASHEET

Motor Feedback Absolute Encoder AD58S DRIVE-CLiQ

EXAMPLE OF INSTALLATION



- * Drehmomentstützen-Ausgleichsmaß von Montage/- und Betriebstoleranzen und thermischen Ausdehnungen.
Max. zulässige Wellenbewegung / Vorspannung Drehmomentstütze.
Statisch ±0.5mm
- * Tether dimension compensation of mounting/- and operating-tolerances and thermal expansions.
max. permissible shaft movement / pretensioning tether.
Static ±0.5mm.

Dimensions in mm

ORDERING INFORMATION AD58 DRIVE-CLiQ

Type	Resolution	Supply voltage	Flange, Protection, Shaft	Interface	Connection
☐	☐	☐	☐	☐	☐
AD58S	0020 20 Bit ST 0024 24 Bit ST 1220 12 Bit MT + 20 Bit ST 1224 12 Bit MT + 24 Bit ST	E DC 10 - 30 V	2.1K Spring Tether, IP50, Taper 1:10	DQ DRIVE-CLiQ	3 PCB Connector, axial

TECHNICAL DATASHEET

Motor Feedback Absolute Encoder AD58S DRIVE-CLiQ Accessories

CONNECTING CABLES




Connecting cable with plug (socket) on both end matching to supply voltage / communication	Ordering Code
M12 Connector, 8-pole, Flange Socket, FEP-Cable, 0,15 m	1 580 022
M12 Connector, 8-pole, Flange Socket, FEP-Cable, 0,20 m	1 580 023
M12 Connector, 8-pole, Flange Socket, FEP-Cable, 0,30 m	1 580 024

ELECTRICAL CONNECTIONS

M12 Connector, 8-pole, Flange Socket

PIN	Signale
1	UB +
2	N.C.
3	RX-P
4	RX-N
5	UB -
6	TX-N
7	TX-P
8	N.C.



Connecting cable with plug (socket) on one end matching to temperature sensor	Ordering Code
2-pole, Cable 0,23 m	1 580 021

ELECTRICAL CONNECTIONS

Temperature Sensor

Colour	Signals
Green	T +
Brown	T -

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: hro@nt-rt.ru || сайт: <https://hengstler.nt-rt.ru>